

Title Block	Template Category	Self Drilling Fasteners - RC
Title Block	Category Description	Fasteners suitable for self drilling, threadforming and sealing in roof and wall cladding applications
Title Block	Template Version	1
Title Block	Suitability of Use	For fastening steel sheeting or steel lined composite panels to steel/ timber substructures. These connections can be internal or external applications and their use comprises connections with predominatly static loads.

Title Block	Parameter Name/ Question	Value/ Answer	Units	Notes
Manufacturers Data	Manufacturer	SFS intec Ltd	Text	
Manufacturers Data	Manufacturer Website	<a href="http://www.sfsintec.co.uk">www.sfsintec.co.uk</a>	URL	
Manufacturers Data	Product Range	SXC14	Text	
Manufacturers Data	Product Model Number	No Performance Declared	Text	Values cover complete product range
Manufacturers Data	Product Literature	<a href="#">SFS intec catalogue</a>	URL	
Manufacturers Data	Features	Composite panel fastener with thread free zone for effective sealing and sheet support	Text	
Manufacturers Data	ISO 9001	<a href="http://www.sfsintec.co.uk/quality_management">www.sfsintec.co.uk/quality_management</a>	URL	
Manufacturers Data	CE Mark	Yes	Text	
<b>Application Data</b>				
Application Data	Roof or Wall Coverings	Roof and Wall	Text	
Application Data	System Type	Composite	Text	
Application Data	Sub structure material	Steel - hot rolled, Aluminium	Text	
Application Data	Environmental Corrosion Category to BS EN12944	C1,C2,C3,C4,C5,C5i	Text	
Application Data	Estimated Service Life C3 (BS ISO 15686-1:2011)	50	Up to Years	
Application Data	Warranty C3	40	Years	
<b>Dimensional Data</b>				
Dimensional Data	Thread Diameter	5.5	mm	
Dimensional Data	Drive Position	External	Text	
Dimensional Data	Head Style	Hex 8mm	Text	
Dimensional Data	Length	80,100,120,140,165,190,215,240,275,305,350	mm	
Dimensional Data	Washer Dimension	16,19,29	mm	
Dimensional Data	Effective Thread Length	29-312	mm	
Dimensional Data	Drilling Capacity - Aluminium	5mm - 14,00mm	mm	
Dimensional Data	Drilling Capacity - Steel	4.0 - 14.0	mm	
Dimensional Data	Product Weight per 100	1.569 to 5.838	kg	
<b>Technical Data</b>				
Technical Data	Powder Coated Head/ Washer	Option	Text	Available to any RAL, BS or NCS colour
Technical Data	European Technical Approval (ETA)	<a href="#">ETA-13/0183</a>	URL	
Technical Data	Declaration of Performance (DoP)	<a href="#">100144457</a>	URL	
Technical Data	Fastener Surface Coating	Zinc Flash	Text	
Technical Data	Fixing Material	Austenitic Stainless Steel - Bimetal	Text	
Technical Data	Fixing Material Grade	304/A2, 316/A4	Text	
Technical Data	Fixing Material Grade to EN standard	EN1.4567, EN1.4401	Text	
Technical Data	Shear Performance	12,400	Newtons	
Technical Data	Tensile Performance	14,000	Newtons	
Technical Data	Free Spin Zone	Yes	Text	
Technical Data	Bending Form Performance (80mm panel)	10	mm	
Technical Data	Washer Material - Metal	Austenitic Stainless Steel	Text	
Technical Data	Washer Material Metal Grade	304/A2, 316/A4	Text	
Technical Data	Washer Material Metal Grade to EN standard	EN1.4567, EN1.4401	Text	
Technical Data	Washer Material - Sealing	Vulcanised EPDM	Text	
<b>Classification Data</b>				
Classification Data	Uniclass 2015	Pr_20_29_76_76	Text	
Classification Data	Uniclass 2015 Description	Self-drilling sheet metal screws	Text	
<b>Sustainability Data</b>				
Sustainability Data	Country of Manufacture	Switzerland	Text	
Sustainability Data	Environmental Product Declaration	No Performance Declared	URL	

#### Information and Accuracy

The details stated are results of tests and/or calculations and therefore are non-binding and do not represent guaranties or warranted characteristics for none-specified applications. All calculations therefore have to be checked and approved by the responsible planner ahead of execution. The user is responsible to assure compliance with all applicable laws and regulations.